



portata S.W.L. kg	sbraccio S span m	H totale height m	h sotto- trave under beam mm	codice colonna code column	h1 mm	A mm	B mm	C mm	D mm	□ P mm	T IPE	T HEA	peso kg
250	3	3	2410	T0230A30	2040	250	600	680	170	350	160		197
	4	3	2410	T0230B40	2040	250	600	680	170	350	160		234
	5	3	2280	T0230C50	1890	300	750	805	170	450		133	355
	6	4	3155	T0240E60	2785	400	850	990	170	600		133	560
	7	4	3005	T0240F70	2635	400	1000	1050	170	600		152	640
	8	4	3100	T0240L80	2640	450	880	1170	170	800		152	797
500	3	3	2260	T0530C30	1830	300	750	730	170	450	200		290
	4	4	3155	T0540E40	2725	400	850	859	170	600	200		480
	5	4	3155	T0540E50	2725	400	850	930	170	600		133	530
	6	4	3100	T0540L60	2730	450	850	880	170	800		152	720
	7	4	3000	T0540L70	2580	450	980	1100	170	800		171	760
	8	4	3000	T0540L80	2480	450	980	1305	170	800		171	1093
1000	3	4	3155	T1040E30	2650	400	850	860	175	600	200		453
	4	4	3100	T1040L40	2655	450	880	910	175	800		152	615
	5	4	3100	T1040L50	2655	450	880	990	175	800		171	698
	6	4	3100	T1040L60	2405	450	880	1185	175	800		171	1000
	7	4	3000	T1040L70	2405	500	980	1250	175	900		190	1095
	8	4	3000	T1040L80	2305	500	980	1330	175	900		190	1165
2000	3	4	3100	T2040L30	2540	450	880	975	240	800		160	625
	4	4	3100	T2040L40	2290	500	880	1115	240	900		180	885
	5	4	3000	T2040L50	2190	500	980	1210	240	900		200	965
	6	4	3000	T2040L60	2190	550	980	1270	240	1000		200	1250
	7	4	3000	T2040L70	2190	550	980	1270	240	1000		220	1250
	8	4	3000	T2040L80	2190	550	980	1270	240	1000		220	1250

* Tutti i dati in tabella sono indicativi e non impegnativi