



PORTATA CAPACITY kg	500	1.000	1.500	2.000	3.000	5.000	10.000	20.000
CARRELLO TROLLEY tipo type	CM005	CM010	CM015	CM020	CM030	CM050	CM100	CM200
svolgimento catena per spostamento di m 5 lift with 5 mt. of hand control chain mm	1.196	1.484	1.507	1.509	1.112	1.110	994	530
sforzo sulla catena effort on the hand control chain kg	2,5	5	7	9	9,5	14	24	25
raggio minimo curvatura - mini radium m	0,8	1	1	1,1	1,3	1,4	2	3,5
A mm	200	246	261	275	333	377	423	555
B mm	67	81	88	94	115	126	155	200
C mm	105	125	132	141	167	192	190	240
D mm	24	27	31	37	39	49	71	92
E mm	14	15	17	20	23	31	50	63
F mm	6	8	10	12	14	16	20	30
G	tirante A - stay mm	169	212	217	237	265	-	-
	tirante B - stay mm	220	262	282	293	303	318	349
	tirante C - stay mm	269	354	384	395	406	418	450
H mm	17	22	22	26	28	38	48	75
I mm	60	60	60	60	60	60	60	90
L mm	6	8	8	10	12	16	30	40
M mm	112	112	112	112	164	164	164	164
N mm	17	19	21	23	26	35	42	53
O mm	30	37	37	36	38	41	42	57
P mm	55	68	74	79	99	109	135	175
Q mm	79	95	102	108	130	144	176	225
R mm	185	220	235	260	310	350	396	500
S mm	99	120	125	132	155	167	200	271
T mm	21	24	24	24	29	31	30	88
U mm	81	97	101	109	129	142	158	208
V mm	40	51	55	64	72	84	105	132
tirante A - stay	ala trave wing rafter	50-100	58-131	70-135	80-143	90-150	-	-
tirante B - stay		50-150	58-200	70-200	80-200	90-200	106-200	120-200
tirante C - stay		50-200	58-300	70-300	80-300	90-300	106-300	120-300
peso carrello trolley weight kg		7	12	14	19	30	44	78